
Specification sheet

page 1 of 1

Properties: AKEMI® Exhaust Putty is a 1-component filler which is free of asbestos. The product is characterized by the following properties:

- no dismantling or welding work
- ready for use
- easy application
- is hardened by the heat of the exhaust
- high gas tightness
- high heat resistance (approx. 700°C)
- high strength
- free of solvents and asbestos

Application areas: AKEMI® Exhaust Putty is used to seal small holes and cracks in car exhausts and flues in domestic heating systems or parts which cannot be repaired with AKEMI® Exhaust Bandage on account of their shape (front end of silencers).

Instructions for use:

1. Clean the area around the hole with a wire brush.
2. Moisten the area to be repaired with a little water.
3. Apply AKEMI® Exhaust Putty onto the area to be repaired and smooth it (approx. 2-4 mm layer).
4. If necessary, AKEMI® Exhaust Putty can be made more pliant with a little water.
5. The car should now be driven a few kilometres at a moderate speed: The hardening results from the heat of the exhaust.

Special notices -

- Wear protective gloves when working with the product.
- Object which have been soiled with AKEMI® Exhaust Putty can be cleaned with water.

Safety notices Please refer to the EC safety data sheet

Technical specifications:

colour:	dark grey
density:	approx. 1.57 g/cm ³
temperature resistance:	approx. 700°C
shelf life:	can be stored for approx. 1 year in the closed original container under cool and frost-free conditions.

Notice: The above information is based on the latest stage of our development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TIS 08.02